



Model	SWT-NS600A	SWT-NS600B	SWT-NS600C	SWT-NS610A	SWT-NS610B	SWT-NS610C
Heating	Double Heating /Welding Rod					
Hot Air Power	1600W	3400W	1600W	1600W	3400W	1600W
Welding Rod Heating Power	800W	800W	800W	800W	800W	800W
Extruding Motor Power	800W	800W	800W	1300W	1300W	1300W
Air Temperature	20-600°C Adjustable					
Extruding Temperature	200-380°C Adjustable					
Driving Motor	HITACHI			METABO		
Voltage	220V 50/60Hz (Customized)					
Temperature Display	Yes					
Motor Cold Start Protection	Yes					
Extruding Volume	2kgs/h	2kgs/h	2kgs/h	2.5kgs/h	2.5kgs/h	2.5kgs/h
Welding Rod Diameter	PP/PE Φ 3 - 4 mm, Φ 5mm (Customized)					
Net Weight	6.0kgs	6.5kgs	6.0kgs	7.0kgs	7.0kgs	7.0kgs
Welding Thickness	1-20mm	8-40mm	1-20mm	1-20mm	8-40mm	1-20mm



Model	SWT-NS600E	SWT-NS610E	SWT-NS610F	SWT-NS620
Heating	Single Heating /Welding Rod			Double Heating / Granules
Hot Air Power	3400W			1600W
Welding Rod Heating Power	No			800W
Extruding Motor Power	800W	800W	1300W	1300W
Air Temperature	20-600°C Adjustable			20-600°C Adjustable
Extruding Temperature	No			800W
Driving Motor	HITACHI	AIRCRAFT	METABAO	METABO
Voltage	220V 50/60Hz (Customized)			220V 50/60Hz (Customized)
Temperature Display	No			Yes
Motor Cold Start Protection	No			Yes
Extruding Volume	2kgs/h	2kgs/h	2.5kgs/h	3.5kgs/h
Welding Rod Diameter	PP/PE Φ 3 - 4 mm, Φ 5mm (Customized)			PP/PE Granules \leq 4mm (Customized)
Net Weight	6.0kgs	6.5kgs	6.0kgs	8kgs
Welding Thickness	1-10mm			5-40mm